

## INSTALLATION INSTRUCTIONS Part Number: SU-7005

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter can last many seasons. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure the K&N® air filter seals properly.

If you need any assistance please call 1-800-858-3333 to speak with a representative in our Customer Service Center before returning the product.

## **INSTALLATION:**

- 1) Remove the stock wing bolt and remove the filter from the air box.
- 2) Clean all sealing surfaces in the air box from any dirt or debris.
- 3) Clean the edge of the K&N filter where the provided gasket will be applied. Fig. 1
- 4) Peel off the adhesive cover from the included gasket and place it over the filter with the sticky side down and slide it down to the flange. Fig. 2

Note that, as the urethane is very slick, the gasket may not fully adhere to it. This is normal and, as the gasket will be sandwiched between the filter and the air box when installed, it will seal as intended.

5) Install the K&N filter into the airbox and secure with the stock wing bolt. Fig 3.

## Available to purchase separately.

Drycharger Wrap; part number SU-7005DK

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1



Fig. 2



Fig. 3

## **CLEANING:**

K&N Engineering, Inc., suggests checking the air filter element periodically for excessive dirt build-up. Depending on your driving conditions, we recommend cleaning your air filter every 50,000 miles. To clean and re-oil, purchase our filter Recharger® service kit, part number 99-5050 or 99-5000 and follow the easy instructions.